epd-norge.no
The Norwegian EPD Foundation

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025

Owner of the declaration	Svenheim Møbelindustri AS
Program holder and publisher	The Norwegian EPD Foundation
Declaration number	NEPD-1430-472-EN
Issue date	17.10.2017
Valid to	17.10.2022

Svenheim

Xena nr 14 bordplate 1800x900x26 rektangulær HVIT - 55105006

Product

Svenheim Møbelindustri AS
Manufacturer



Xena bordplater har kjernemateriale i 25 mm MDF. Denne spesifikke modellen er belagt med høytrykkslaminat K1040UN Alpino, hvit farge RAL 9016/NCS S 0502-G50Y, og har klarlakkert MDF- kant. Kanten er profilert 10 mm rett med 40 grader skrå under

General information

Product
Xena bordplateserie

Owner of the declaration:
Svenheim Møbelindustri AS
Contact person: Agnė Raulonytė
Phonenr. +37065771148
Email: post@svneheim.no

General Information
The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo
Phone: +4723088000
e-mail: post@epd-norge.no

Manufacturer
UAB Svenheim

Declaration number:NEPD-1430-472-EN

Place of production:
Alytus, Lithuania

This declaration is based on Product Category Rules:
PCR for furniture, NPCR 021, Norwegian EPD Foundation

Management system:
ISO 14001, Certificate No. 81858-2010-AE-LUT-FINAS
ISO 9001, Certificate No. 81860-2010-AQ-LTU-FINAS
Accredited unit: DNV Certification OY/AB, Finland

Declared unit:
1800x900x26

Org. No:
No. 950740213

Declared unit with option:

Issue date:
17.10.2017

Functional unit:

Valid to:
17.10.2022

This EPD has been worked out by:
The declaration has been developed using Furniture EPD Tool Version 1.3.2, Approval: NEPDT04
Company specific data collected and registered by:
Data Collector Agnė Raulonytė
Company specific data audited by:
Data Auditor Jan Petter Nilsen

Comparability:
EPDs from programmes other than the Norwegian EPD Foundation may not be comparable

Year of study:
2017

Verification:
Independent verification of data, other environmental information and EPD has been carried out in accordance with ISO14024, 8.1.3. and 8.1.4.

Approved

externally



Mie Vold, Senior Research Scientist
(Independent verifier approved by EPD Norway)



Håkon Hauan
Managing Director of EPD-Norway

Key environmental indicators	Unit	Cradle to Gate A1-A3
Global warming	kg CO_2	38
Total energy use	MJ	1127
Amount of recycled materials	%	2 %

Product


Product Description and Application
Xena bordplater produseres i 26mm tykk MDF med faset kant. Plater i bøk, bjerk, og eik er belagt med lakkert finér. Plater med grå og hvit farge er belagt med høytrykkslaminat.

Technical Data
Total Weight: 27,3 kg (28,1 kg with packaging)

Market
Europe

Reference Service Life
15 years

Materials			Recycled material in manufactured product		Recyclable material at end of product life	
Unit	kg	%	%	kg	%	kg
Wood	26,33	94 %	0 %	0,00	0 %	0,00
Other	1,04	4 %	0 %	0,00	3 %	0,04
Packaging	0,77	3 %	66 %	0,51	100 %	0,77
Total	28,14		2 %		3 %	




Product manufactured from 2% recycled material
At end of life product contains 3% recyclable material

LCA: Calculation rules

Declared Unit
Product of one Xena table 1800x900x26 provided and maintained for a period of 15years

System Boundary
Life cycle stages included are described in figure and through the corresponding letter and number designations in the



Data quality
Specific manufacturing data from 2014 are used. Data from Ecoinvent 3.0.1. and Østfoldforskning databases are used as the basis for raw materials and energy carrier production. See [6].

Cut-off criteria
All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows that are included with very small amounts (<1%) are not included. This cut-off rule does not apply for hazardous materials and substances

Allocation
Where virgin materials are used, emissions and energy consumption connected with extraction and production are included.
Where recycled materials are used in the product, emissions and energy consumption related to the recycling process are included.
Emissions from incineration are allocated to the product system that uses the recovered energy.
Emissions from incineration of waste are allocated to the product system that uses the recovered energy.

LCA: Scenarios and additional technical information

Transportation to an average customer in Norway (Jessheim) is 1306 km
(A4: average European lorry > 32 tonnes) 881,55km by lorry (>32) and 424,45km by sea transport.
In the end of life stage, the transport distance for waste to waste processing is 72 km (C1). The reuse, recovery and recycling stage is beyond the system boundaries (D). It is assumed that the solution is dismantled and the materials recycled or combusted according to the general Norwegian treatment of industrial waste (see the table below). The transport distance to reuse, recovery or recycling is varying for each material, but the average distance is 373 km. The vehicles used and associated data are described in detail in [5].

	Material recovery	Energy recovery	Disposal
Aluminium	70,1 %	0,0 %	30 %
Steel	70,1 %	0,0 %	30 %
Plastic	64,3 %	30,8 %	5 %
Cardboard	94,5 %	5,5 %	0 %

LCA: Results

The following information describe the scenaries in the different modules of the EPD.

System boundaries (X=included, MND=modul not declared, MNR=modul not relevant)

Product stage			Construction stage		Use stage				End of life			Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Construction	Maintenance	Repair	Replacement	Operational energy use	Transport	Waste Processing	Disposal	Reuse-recovery-recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	C1	C2	C3	D
x	x	x	x	MNR	x	MNR	MNR	MNR	x	x	x	x

Environmental impact (INA = Indicator Not Assessed)

Parameter	A1	A2	A3	A1-A3	A4	B1	C1	C2	C3	C1-C3	D
GWP	28,3	4,1	5,3	37,7	2,3	0,0	1,1	1,2	6,5	8,8	-0,8
ODP	3,2E-06	7,8E-07	3,1E-07	4,3E-06	4,4E-07	0,0	INA	INA	INA	INA	-7,2E-08
POCP	1,5E-02	6,9E-04	3,3E-03	1,9E-02	4,4E-04	0,0	INA	INA	INA	INA	-3,4E-04
AP	4,8E-02	3,7E-03	1,8E-02	0,1	2,2E-03	0,0	INA	INA	INA	INA	-1,2E-03
EP	0,2	1,6E-02	2,7E-02	0,2	1,1E-02	0,0	INA	INA	INA	INA	-1,8E-03
ADPM*	1,0E-04	7,6E-06	8,4E-06	1,2E-04	4,2E-06	0,0	INA	INA	INA	INA	-5,5E-06
ADPE	480,6	62,6	63,4	606,6	35,5	0,0	INA	INA	INA	INA	-10,8

GWP Global warming potential (kg CO2-eqv.); ODP Depletion potential of the stratospheric ozone layer (kg CFC11-eqv.); POCP Formation potential of tropospheric photochemical oxidants (kg C2H4-eqv.); AP Acidification potential of land and water (kg SO2-eqv.); EP Eutrophication potential (kg PO4-3-eqv.); ADPM Abiotic depletion potential for non fossil resources (kg Sb -eqv.); ADPE Abiotic depletion potential for fossil resources (MJ);

* Some processes use Ecoinvent 3.0.1. and thus data on renewable resources is omitted. The true ADPM, RPEE, RPEM and TPE may be higher than indicated. This issue will be addressed in a new version of Ecoinvent 3, data from which was not available when this declaration was prepared.

Resource use (INA = Indicator Not Assessed)

Parameter	A1	A2	A3	A1-A3	A4	B1	C1	C2	C3	C1-C3	D
RPEE*	380,8	1,0	63,5	445,2	0,6	0,0	INA	INA	INA	INA	-0,1
RPEM*	262,0	0,3	41,4	303,8	0,2	0,0	INA	INA	INA	INA	-1,0
TPE*	642,8	1,3	104,9	749,0	0,7	0,0	INA	INA	INA	INA	-1,1
NRPE	517,8	63,8	100,5	682,0	36,2	0,0	INA	INA	INA	INA	-10,5
NRPM	5,7	0,0	0,0	5,7	0,0	0,0	INA	INA	INA	INA	0,0
TNRPE	523,5	63,8	100,5	687,7	36,2	0,0	INA	INA	INA	INA	-10,5
SM	0,5	0,0	0,0	0,5	0,0	0,0	INA	INA	INA	INA	0,0
RSF	1,1E-04	0,0	0,0	1,1E-04	0,0	0,0	INA	INA	INA	INA	0,0
NRSF	3,6E-04	0,0	0,0	3,6E-04	0,0	0,0	INA	INA	INA	INA	0,0
W	3,6E-04	0,0	0,0	3,6E-04	0,0	0,0	INA	INA	INA	INA	0,0

RPEE Renewable primary energy resources used as energy carrier (MJ); RPEM Renwable primary energy resources used as raw materials (MJ); TPE Total use of renewable primary energy resources (MJ); NRPE Non renewable primary energy resources used as energy carrier (MJ); NRPM Non renewable primary energy resources used as materials (MJ); TNRPE Total use of non renewable primary energy resources (MJ); SM Use of secondary materials (kg); RSF Use of renewable secondary fuels (MJ); NRSF Use of non renewable secondary fuels (MJ); W Use of net fresh water (m3);

End of life - Waste and Output flow (INA = Indicator Not Assessed)

Parameter	A1	A2	A3	A1-A3	A4	B1	C1	C2	C3	C1-C3	D
HW	4,3E-03	3,7E-05	1,2E-04	4,5E-03	2,1E-05	0,0	INA	INA	INA	INA	0,0
NHW	11,9	5,8	1,3	19,1	3,2	0,0	INA	INA	INA	INA	-0,1
RW	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0
CR	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0
MR	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0
MER	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0
EEE	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0
ETE	0,0	0,0	0,0	0,0	0,0	0,0	INA	INA	INA	INA	0,0

HW Hazardous waste disposed (kg); NHW Non hazardous waste disposed (kg); RW Radioactive waste disposed (kg); CR Components for reuse (kg); MR Materials for recycling (kg); MER Materials for energy recovery (kg); EEE Exported electric energy (MJ); ETE Exported thermal energy (MJ);

Specific Norwegian requirements

Electricity

The electricity consumed is assumed to be from East pool mix in the East European countries. European mix and energy mix in Lituania is based on data from the Wold bank. (Based on data 2011.)

Electricity mix: 0,053 kg CO2 eqv/MJ (East Europen mix)

Dangerous Substances

None of the following substances have been added to the product: Substances on the REACH Candidate list of substances of very high concern (of '16.06.2014) substances on the Norwegian Priority list (pr.17.06.2013) and substances that lead to the product being classified as hazardous waste. The chemical content of the product complies with regulatory levels as given in the Norwegian Product Regulations

Indoor Environment

According to ISO 14001

Climate Declaration

Not relevant

Bibliography

[1] NS-EN ISO 14025:2006, Environmental labels and declarations-Type III environmental declarations-Principles and procedures.

[2] NS-EN ISO 14044:2006, Environmental management - Life cycle assessment - Requirements and guidelines

[3] EN 15804:2012 + A1:2013 Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products

[4] Product category rules (PCR) for preparing an environmental product declaration for: Product Group Seating Solution NPCR 003: 2015; Product Group Plate Furniture NPCR 021: 2012

[5] Raadal, H. L., Modahl, I. S., Lyng, K. A. (2009). Klimaregnskap for avfallshåndtering, Fase I og II. OR 18.09. ISBN : 978-82-7520-611-2, 82-7520-611-1

[6] Brekke, A., Møller, H., Baxter, J., Askham, C. (2014). Verktøy - miljødeklarasjon for møbel Dokumentasjon som grunnlag for verifisering, Ostfold Research

epd-norge.no The Norwegian EPD Foundation	**Program Holder and Publisher** The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo Norge	Phone: +4723088292 email: post@epd-norge.no web: www.epd-norge.no
Svenheim	**Owner of the Declaration** Svenheim Møbelindustri AS Ulefossveien 48 3730 SKIEN - Norway	Phone: +4781570790 email: post@svenheim.no web: www.svenheim.no
Østfoldforskning	**Author of the Life Cycle Assessment** Østfoldforskning AS Stadion 4 1671 Kråkerøy	Phone: +4769351100 email: post@ostfoldforskning.no web: www.ostfoldforskning.no